


| | | |
|---|----------------------------|-------------------------------------|
|  <p>EMC Shielding Effectiveness Test Report EMI ECE Gaskets TO MIL-DTL-83528E</p> | <i>Report No.</i> 20937 | <i>Issue Date</i> April 24, 2015 |
| | <i>Revision</i> 1.0 | <i>Page</i> 12 of 22 |

APPENDIX C - Supplemental Data

| | |
|--------------------------|--------------------------|
| <i>Minimum</i> | <i>Best-Case</i> |
| <i>Attenuation Level</i> | <i>Attenuation Level</i> |
| <i>(dB)</i> | <i>(dB)</i> |
| 79.6 @ 200kHz | 148.2 @ 1000MHz |

| | | |
|--|---------------|---------------------------------------|
| Shielding Effectiveness Frequency (MHz) | Dynamic Range | 806-XXXX-517-651 (SE) (Material A) |
|--|---------------|---------------------------------------|

| | | |
|--------|-----|-------|
| 20 | 130 | 126.5 |
| 30 | 130 | 126.9 |
| 40 | 140 | 137.8 |
| 60 | 140 | 138.8 |
| 80 | 150 | 147.5 |
| 100 | 150 | 143.7 |
| 200 | 150 | 147.5 |
| 400 | 150 | 143.4 |
| 600 | 150 | 146.1 |
| 800 | 150 | 147.5 |
| 1000 | 150 | 148.2 |
| 2000 | 125 | 126.4 |
| 4000 | 120 | 119.2 |
| 6000 | 120 | 118.7 |
| 8000 | 120 | 119.4 |
| 10000 | 120 | 119.1 |
| 200kHz | 80 | 79.6 |